

Figure 4.10. Bridge vertical clearance locations for first and last girder.....	137
Figure 4.11. NCDOT special survey of vertical clearance at selected bridges.....	138
Figure 4.12. Schematic of minimum (MVC) and maximum-minimum (MMVC) vertical clearance for; (a) signs and (b) bridges.....	139
Figure 4.13. Survey and Geo-3D measurement locations for Glen Eden Drive bridge.	140
Figure 4.14. Terrametrix measurement locations for Glen Eden Drive bridge.	141
Figure 4.15. Survey and Geo-3D measurement locations for Lake Wheeler Road bridge.	142
Figure 4.16. Terrametrix measurement locations for Lake Wheeler Road bridge.	142
Figure 4.17. Measurement locations for South Saunders Street exit sign.	143
Figure 5.1. Hierarchy of physical risk parameters and their Factors (ADT =Average daily traffic and AADT =average annual daily traffic), [Zayed et al. 2007].....	148
Figure 5.2. The pulse-echo method [LADOTD and FDC 2008].....	150
Figure 5.3. Borehole setup for unknown foundation determination by parallel seismic method: (a) parallel seismic survey setup and (b) parallel seismic data [USDOT 2008].....	151
Figure 5.4. Retaining walls for study: (a) US1/NC98 and (b) US147 Hillandale wall.	156
Figure 5.5. Geometry of US70/I85 retaining wall (front view with sloped Face at H:V=1:3)...	157
Figure 5.6. LIDAR mapping of US-147 Hillandale MSE wall.	157
Figure 5.7. Longitudinal bridge profiles by LIDAR and Profilemeter: (a) US 64 over railroad and (b) US 64 over Smithfield road.....	160
Figure 5.8. LIDAR image of US-64 bridge over railroad.....	160
Figure 5.9. IRI variation for the selected cases.....	162
Figure 5.10. PSR variation for the selected cases.....	162